

# SANTA REINDEER WALL HANGING

## Read both sets of instructions before your begin

### TO GET OESD DIRECTIONS FOR THE REINDEER WALL HANGING

Go to [www.embroideryonline.com](http://www.embroideryonline.com), type the pack number 12272 into the search bar at the top and click "Search", click on the pack number (in red text) beneath any of the designs, and then select "View Pack PDF" (also in red text) at the top of the page. The instructions and thread chart are printable, so they can be stored on your computer in the electronic file or printed for a hard copy.

### Constructions instructions:

*Start with a new needle a walking foot and the needle in the down position.*

1. Cut the blocks with at least a ½ inch seam allowance.
2. Lay out the blocks in order
3. Adjust your stitch length to 2.8 or 3. Back stitch or lock stitch at the beginning and end of each seam, stopping at the block outline stitching.
4. Start construction with the two blocks that say Merry Christmas.
5. Start by joining the vertical sides
6. Place basting tape on one side –do not cover the outline stitching on the block
7. Line up the next block over the first – making sure the lines all match. The tape will allow you to flip the seam open to view your matching. There needs to be at least a stitch width space between the two blocks.
8. Stitch the seam
9. Open the seam and finger press both sides. Remove the tape at this time. If it is caught in the seam, just finger press the seam open as best as you can. Audition the "window" tape to be sure that the lettering on the Merry Christmas is not covered up.
10. Repeat the above until the first row is complete.
11. Join the other rows in the same manner. Check to be sure that the horizontal lines match on each row.
12. Before joining the rows finger press all seams again.
13. Join the rows to each other in the appropriate sequence.
14. Finger press the seams open on the front and back
15. Spray baste the batting to the sewn panel. Start at the top and be sure the seams are laying open as you proceed to spray.
16. Spray baste the Peltex or other heavy interfacing to the batting. It you have used cutaway stabilizer this step is not necessary. If you prefer your hanging to be less stiff skip this step.
17. Stitch three (top, batting, and peltex),layers together by stitching in the ditch on all lines.
18. Spray baste the backing to the sandwich.
19. Pin at the edges.
20. Attach the window pane bias using a zigzag stitch adjusted to 4.0/3.0.
21. Start in the middle of the row and stitch to the outside. The tape tends to walk.
22. Robison Anton metallic gold blends into the clover gold quick bias.
23. Bind the wall hanging using your favorite technique.
24. Attach loops or other method for hanging.